

Rittal – The System.

Faster – better – everywhere.

Captive nut – EL 2092.200

Date : Mar 19, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Captive nut – EL 2092.200

created: 19.03.2018 build on www.rittal.com/us-en



Product description

Version: Without contact

Description: To fasten slide-in electronic equipment, 482.6 mm (19") installed equipment and blanking plates to profile rails. Used with profile plate thicknesses 0.8 – 2.0 mm. For narrow tolerances, captive nuts for profile plate thicknesses 1.2 – 1.5 mm should be used. Either with or without contacting the installed equipment with the 482.6 mm (19") profile/housing.

Product features

Thread: Type: M6

For plate thicknesses: 0,8 mm - 2 mm

Packaging unit: 50 pc(s).

Weight/packaging unit: 0.2 kg (0.4 lb.)

EAN: 4028177014114

Customs tariff number: 73181692

ETIM 6.0: EC002358

ETIM 5.0: EC002358

eCl@ss 8.0/8.1: 23110815

eCl@ss 7.0/7.1:	27182590
eCl@ss 6.0/6.1:	27182590
eCl@ss 5.1/5.1.4:	27182504
Product description (long):	EL Captive nuts, M6, Without contact, For metal thickness: 0,8-2 mm