

Rittal – The System.

Faster – better – everywhere.

TS punched rail, 18 x 38 mm – TS 8612.280

Date : Mar 19, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TS punched rail, 18 x 38 mm – TS 8612.280

created: 19.03.2018 build on www.rittal.com/us-en



Product description

Description: Simply locate and secure with a screw. Location system makes installation and removal easy. Only needs to be secured on one side, but can be secured on both sides if necessary.

Material: Carbon steel

Supply includes: Assembly screws

Note: In enclosures with a mounting plate, two punched rails are already included in the scope of supply.

Product features

Suitable for: Width/depth: 800 mm

Installation options:
On the vertical TS, SE enclosure section on the outer mounting level
On the horizontal TS, SE enclosure section
On base configuration rail for CM

Packaging unit: 4 pc(s).

Weight/packaging unit: 3.7 kg (8.1 lb.)

EAN: 4028177213111

Customs tariff number: 73269098

ETIM 6.0: EC002625

ETIM 5.0:	EC002625
eCl@ss 8.0/8.1:	27189234
eCl@ss 7.0/7.1:	23159101
eCl@ss 6.0/6.1:	23159101
eCl@ss 5.1/5.1.4:	27189232
Product description (long):	TS Punched rail 18 x 38 mm, for W/D: 800 mm
Approvals	
Certificates:	EAC