

Rack PDU, Basic, 1U, 16A, 208/230V, (12)C13
AP9565

In Stock
\$159.99*



- Reliable rack power distribution
- Includes: Installation Guide, Rack Mounting Brackets

Output	
Nominal Output Voltage	208V, 230V
Maximum Total Current Draw	16
Output Connections	(12) IEC 320 C13 (Battery Backup)

Input	
Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	IEC-320 C20
Cord Length	8.2ft (2.5meters)
Number of Power Cords	1
Load Capacity	3680VA
Maximum Input Current	16A

Physical	
Maximum Height	1.75inches (44MM, 4.4CM)
Maximum Width	17.6inches (447MM, 44.7CM)
Maximum Depth	2.25inches (57MM, 5.7CM)
Rack Height	1U
Net Weight	4.5lbs. (2.05KG)
Shipping weight	8.0lbs. (3.64KG)
Shipping Height	2.75inches (70MM, 7.0CM)
Shipping Width	18.25inches (464MM, 46.4CM)

*Prices are indicative

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Rack PDU, Basic, 1U, 16A, 208/230V, (12)C13 | AP9565 | Downloaded on 05/23/2020 (EST)

Physical

Shipping Depth	9.0inches (229MM, 22.9CM)
Color	Black

Environmental

Operating Temperature	32 - 113 °F (0 - 45 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-10000ft (0-3000meters)
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-50000ft (0-15000meters)

Conformance

Approvals	cUL Listed, CE, Queensland Australia, UL 60950, UL Listed, VDE
Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs
PEP	Available in Documentation tab
EOL	Available in Documentation tab

*Prices are indicative

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.