

Rittal – The System.

Faster – better – everywhere.



FlatBox – DK 7507.120

Date : Apr 2, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



FlatBox – DK 7507.120

created: 02.04.2020 on www.rittal.com/com-en



Product description

| | |
|-------------------------|---|
| Design: | with 482.6 mm (19") mounting frame |
| Description: | For flexible use as a wall-mounted or floor-standing enclosure. |
| Benefits: | Tool-free quick assembly System assembly on the open 482.6 mm (19") frame |
| Material: | Sheet steel Viewing window: Single-pane safety glass, 3 mm |
| Surface finish: | Powder-coated |
| Colour: | RAL 7035 |
| Supply includes: | Flat-packed enclosure 1 wall section 2 basic supports 2 roof/base plates, with cut-outs for cable entry via brush strips 2 side panels, lockable 1 glazed door, lockable, security lock 3524 E, door hinge point selectable Connection components for tool-free, fast assembly Earthing kit for system-compatible earthing of all enclosure parts 482.6 mm (19") mounting frame |
| Note: | Max. installation depth: Depth - 58 mm to rear panel Max. distance between two 482.6 mm (19") levels: Depth - 104 mm |
| Basic material: | Sheet steel |

Product features

| | |
|--|---|
| Dimensions: | Width: 600 mm Height: 625 mm Depth: 600 mm |
| Installation height for components: | 12 U |
| Outlet direction: | For flexible use as a wall-mounted or floor-standing enclosure. |
| Load capacity: | Max. 600 N |
| Packs of: | 1 pc(s). |
| Weight/pack: | 31 kg |
| EAN: | 4028177551459 |
| Customs tariff number: | 94032080 |
| ETIM 7.0: | EC002500 |
| ETIM 6.0: | EC002500 |
| eCl@ss 8.0/8.1: | 27180208 |
| eCl@ss 6.0/6.1: | 27180208 |
| Product description: | DK FlatBox, WHD: 600x625x600 mm, 12 U, with 482.6 mm (19") mounting frame |