



**7712135**

DK 12u distribution enc RAL 7035



# Technical

|                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>                          | Wall-mounted enclosure with optimum accessibility due to hinged part.                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Material</b>                             | Wall and hinged part: Sheet steel, 1.5 mm<br>Viewing window: Single-pane safety glass, 3 mm                                                                                                                                                                                                                                                                                                                                                             |
| <b>Surface finish</b>                       | Powder-coated                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Colour</b>                               | Wall and hinged part: RAL 7035<br>Glazed door: RAL 7035/7015 (slate grey)                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Protection category IP to IEC 60 529</b> | IP 55                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Supply includes</b>                      | Wall section<br>Hinged part with 25 mm pitch pattern of holes in the front and rear frame<br>Designer glazed door<br>Wall section: Gland plate, solid, top and bottom<br>Wall section: 2 vertical punched rails<br>Wall section: C rail mounted horizontally for cable clamping<br>1 Hinged part with two 482.6 mm (19") mounting angles, fully depth adjustable<br>4 4 wall mounting brackets 10 mm<br>1 Mini-comfort handle<br>1 Security lock 3524 E |
| <b>Design</b>                               | with punched rails and mounting angles, depth-variable                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Basic material</b>                       | Sheet steel                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Dimensions</b>                           | Width: 600 mm<br>Height: 612 mm<br>Units: 12 U<br>Depth: 473 mm                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Depth hinged part</b>                    | 316 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Installation depth</b>                   | 420 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Clearances</b>                           | Clearance width: 502 mm<br>Clearance height: 549 mm                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Wall section</b>                         | Depth: 135 mm                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Load capacity</b>                        | Hinged part, static (max.): 600 N                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Packs of</b>                             | 1 pc(s).                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Weight/pack</b>                          | 36 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>EAN</b>                                  | 4028177324190                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Customs tariff number</b>                | 94032080                                                                                                                                                                                                                                                                                                                                                                                                                                                |

Braithwell Way, Hellaby Industrial Estate  
Hellaby, Rotherham  
T: 01709 704000 E: [csd@rittal.co.uk](mailto:csd@rittal.co.uk) W: <http://www.rittal.co.uk>

|                         |          |
|-------------------------|----------|
| <b>ETIM 6.0</b>         | EC000261 |
| <b>ETIM 5.0</b>         | EC002500 |
| <b>eCl@ss 8.0/8.1</b>   | 27142408 |
| <b>eCl@ss 7.0/7.1</b>   | 27180208 |
| <b>eCl@ss 6.0/6.1</b>   | 27180208 |
| <b>eCl@ss 5.1/5.1.4</b> | 27180204 |

Datasheet generated from <https://onetimepim.com> last updated Thursday, January 23, 2020 11:01:13 AM